

CLAIMS

Having thus described the invention, what is claimed is the following:

- 1 1. A space-saving scanner assembly, comprising:
2 a housing having a substantially vertical source-contact surface with a channel
3 extending therefrom; and
4 a flap coupled to the source-contact surface, the flap having a source-backing
5 surface substantially parallel to the source-contact surface of the housing, wherein the
6 source-contact surface, the source-backing surface, and the channel form an opening
7 for receiving an edge of a source to be scanned.
- 1 2. The assembly of claim 1, wherein a portion of the vertical source-
2 contact surface of the housing comprises a platen to permit scanning of a source
3 document in a vertical position.
- 1 3. The assembly of claim 1, wherein the housing contains a front panel
2 with an inclined surface adjacent to the opening, the inclined surface forming a wider
3 opening at the surface of the front panel.
- 1 4. The assembly of claim 1, wherein the flap includes an inclined surface
2 adjacent to the opening, the inclined surface arranged to increase the opening along a
3 front edge of the flap, wherein the front edge is substantially perpendicular to the
4 source-backing surface.
- 1 5. The assembly of claim 1, wherein the flap includes a slot.
- 1 6. The assembly of claim 1, wherein the flap includes a clip arranged to
2 receive a portion of a source to be scanned.

1 7. The assembly of claim 1, wherein the housing further comprises a
2 recess configured to receive a portion of the channel when the source-backing surface
3 is in close proximity to the source-contact surface.

1 8. The assembly of claim 2, wherein the platen has an upper edge, an
2 opposing lower edge, a front edge relatively coexistent with a front panel of the
3 housing and a distal edge and wherein the channel is adjacent to the lower edge of the
4 platen.

1 9. The assembly of claim 8, wherein the channel has a first end proximal
2 to a front panel of the housing and a distal end that extends at least to the distal edge
3 of the platen.

1 10. The assembly of claim 1, wherein the flap is coupled to the housing
2 with at least one post assembly having a plurality of spatially-separated detent
3 positions.

1 11. The assembly of claim 1, wherein the flap is coupled to the housing
2 with at least one adjustable fastener for closely contacting the source-backing surface
3 to the source-contact surface.

1 12. The assembly of claim 5, wherein the slot is positioned to permit the
2 placement of a relatively short source document on edge on the channel wherein
3 information to be scanned is aligned with at least a portion of the platen.

1 13. The assembly of claim 1, wherein the housing is configured to extend
2 the channel from the source-contact surface when an operator adjusts the source-
3 backing surface in relation to the source-contact surface to increase the width of the
4 opening.

1 14. The assembly of claim 1, wherein the width of the proximal end of the
2 channel increases over that portion of the channel that extends beyond the platen.

1 15. The assembly of claim 1, wherein the channel is coated with a material
2 having a relatively low coefficient of friction.

1 16. A space-saving scanner assembly, comprising:
2 means for optically scanning and converting image data into a digital data
3 representation of a source;
4 means for spatially adjusting a source to be scanned with the means for optical
5 scanning; and
6 means for supporting the source along an edge of said source during a
7 scanning operation.

1 17. The assembly of claim 16, wherein the source edge support means
2 comprises a channel.

1 18. The assembly of claim 16, wherein the adjusting means comprises a
2 slot.

1 19. The assembly of claim 16, wherein the adjusting means comprises a
2 first inclined surface associated with a housing and a second inclined surface
3 associated with a flap.

